Cavium OCTEON TX- ARM Powered Desktop Networking Appliance

# Interface Masters TECHNOLOGIES Innovative Network Solutions


#### **OVERVIEW**

Interface Masters Technologies presents Tahoe 8822, a highly flexible mand expandable 1U networking appliance with the lowest OPEX. It is based on Cavium 64-bit ARMv8 technology. It supports DPDK for applications that require highly efficient data processing. Tahoe 8822 supports CN83xx family of processors. It features a small form factor, twelve 1/10GE SFP+ ports, an SD card, and two USB 3.0 host ports. Customization services are offered

Interface Masters Technologies provide support for the Cavium SDK on multiple Linux distributions. Additional software and firmware enable rapid application development. Interface Masters offers Layer 1 and 2 supports as well as software application development capabilities.

#### Target Applications include:

- Network Security Appliances such as Unified Treat Management (UTM)
- Intrusion Detection System (IDS)
- Intrusion Prevention System (IPS)
- Intelligent Edge Appliance (IEA)
- Data Loss Prevention (DLP)
- Content Management System (CMS)
- Network Offload Assist
- SSL/IPSec offload processing
- WAN optimization
- Application Delivery Controllers
- Custom Networking Appliance



Block Diagram of Tahoe 8822



Tahoe 8822 ISO View

## PRODUCT FEATURES

### **CPU**

 Cavium OCTEON TX CN8360 (18 Core at 800/1,000/1,200/1,500 MHz)

#### DRAM

- Two of DDRIIII SODIMM, up to 16GB ECC None Volatile Memory
- SPI NOR Flash
- eMMC
- SATA 3.0

#### I/O Interfaces

- 12 x 1/10GE SFP+ ports
- 1 x 10/100/1000 management port
- 1 x RS232 console port
- 2 x USB 3.0

#### **Functions**

- Real time clock
- Temperature sensor
- Optional TPM

## **Power Supplies**

Two internal redundant power supplies

## **Operating System**

Linux Cavium SDK

ENVIRONMENTAL		
Operating Temperature	0° to 40 °C (32° to 104°F)	
Storage Temperature	-40° - 85°C (-4°F to 185°F)	
Operating Humidity	10 to 90%, relative humidity non-condensing	
Storage Humidity	5 to 95% relative humidity non- condensing	

DIMENSIONS (Preliminary)		
	Inches	Millimeter
Length	10.00	254
Height	1.73	44
Width	7.50	190

OPTIONAL ACCESSORIES	
Tahoe8822-ACS02	19" Rack mounting tray

ORDERING INFORMATION		
Part Number	Description	
Tahoe8822- CN8360-800	Tahoe 8822 with OCTEON TX CN 8360 at 800 MHz	
Tahoe8822- CN8360-1,000	Tahoe 8822 with OCTEON TX CN8360 at 1,000 MHz	
Tahoe8822- CN8360-1,200	Tahoe 8822 with OCTEON TX CN 8360 at 1,200 MHz	
Tahoe8822- CN8360-1,500	Tahoe 8822 with OCTEON TX CN 8360 at 1,500 MHz	

## **CUSTOMIZATION SERVICES**

Hardware, Firmware, Linux O/S and application code development services available.



## ABOUT INTERFACE MASTERS TECHNOLOGIES, INC.

Interface Masters Technologies is a leading provider of high-speed networking solutions focused on 1/10 /25/40/100/200 Gigabit Ethernet networking solutions. For over 25 years, Interface Masters Technologies has been providing innovative networking solutions with customization services to OEMs, large enterprises and sophisticated end users. Interface Masters Technologies provides Ethernet switches, appliances, server adapter cards with high port density, networking offload and bypass functionality. Company headquarters are located in San Jose, CA with satellite offices in Hong Kong and Europe.

Address: 150 East Brokaw Rd., San Jose, CA 95112

Phone: 408-441-9341 Fax: 815-364-0888 Email: sales@interfac

Email: sales@interfacemasters.com Web: www.interfacemasters.com

